

	Beistellkessel rund, indirekt beheizt						Beistellkessel eckig, indirekt beheizt				Kochkessel				
	6080100	6080100-FB	6080200	6080200-FB	6080300	6080300-FB	6080500	6080600	60806-KA10	6080700	6080800	6080800-FB	6080900-003	6080900-003-FB	6080900
Kesselinhalt Liter	90	90	120	120	150	150	120	150	150	200	300	300	300	300	400
Innenkesselform	●	●	●	●	●	●	●	●	●	●	■	■	■	■	■
Beheizung	—	—	—	—	—	—	—	—	—	—	→	→	—	—	→
Glyzerinfüllung in kg	32	32	38	38	44	44	38	38	44	44			60	60	
Thermostatische Regelung	✓	✓	✓	✓	✓	✓	✓	✓							
Mikroprozessor- Steuerung									✓	✓	✓	✓	✓	✓	✓
Anschlußwert 380/400 V	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Heizleistung in kW	6	6	9	9	9	9	9	9	9	12	17	17	27	27	21
Festanschluss											✓		✓		✓
CEE-Stecker 16/32 A	16	16	16	16	16	16	16	16	16	32		32		64	
sep. Schaltkasten											✓		✓	✓	✓
Integrierter Schaltkasten												✓			
Außenabm. B (über alles)	770	770	820	820	920	920	700	700	700	850	1115	1495	1115	1495	1365
Außenabm. T (über alles)	800	800	850	850	850	850	840	840	840	1020	1200	1200	1178	1178	1200
Arbeitshöhe in mm	860	860	860	860	860	860	920	920	920	920	955	955	1020	1020	955
Innenabmessung Breite in mm											900	900	900	900	1150
Innenabmessung Tiefe in mm											800	800	800	800	800
Innenabmessung Höhe in mm	530	530	530	530	530	530	530	530	530	530	450	450	450	450	450
Innenabmessung Durchmesser in mm	480	480	540	540	600	600	540	600	600	700					
Auslaufhahn	1 ¼"	1 ¼"	1 ¼"	1 ¼"	1 ¼"	1 ¼"	1 ¼"	1 ¼"	1 ¼"	1 ½"	1 ½"	1 ½"	1 ½"	1 ½"	1 ½"
Stationär	✓		✓		✓						✓		✓		✓
Fahrbar		✓		✓		✓	✓	✓	✓	✓		✓		✓	
Aufheizzeit 20°-90° in Min	97	97	95	95	120	120	90	115	115	100	95	95	110	110	105
Wasserzulauf							○	○	○	○	○	○	○	○	○
Kerntemperaturfühler									○	○	○	○	○	○	○
Signalhupe									○	○	○	○	○	○	○